

# OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - March 2024										
EN	ASTM	OSTP	Currency / Kgs				Old Ref GRADE	CR	NI	MO
			EUR	GBP	USD	SEK				
1.4301	304	4301	2.323	1.985	2.510	26.271	17-9	18.0	8-9	
1.4307	304L	4307	2.323	1.985	2.510	26.271	18-8L	18.0	8-9	
1.4306	304L	4306	2.548	2.178	2.754	28.819	18-10L	18.0	10.0	
1.4541	321	4541	2.521	2.154	2.723	28.500	18-10Ti	17.0	9.0	
1.4401	316	4401	3.797	3.245	4.104	42.944	17-11-2	16.5	10.0	2.0
1.4404	316L	4404	3.797	3.245	4.104	42.944	17-11-2L	16.5	10.0	2.0
1.4571	316Ti	4571	3.847	3.288	4.157	43.503	17-11-2Ti	16.5	10.5	2.0
1.4436	316	4436	4.142	3.540	4.476	46.842	17-11-2.5	16.5	10.5	2.5
1.4432	316L	4432	4.216	3.603	4.556	47.676	17-12-2.5L	16.5	10.5	2.5
1.4435	316L	4435	4.275	3.652	4.618	48.332	17-13-2.5L	17.0	12.5	2.5
1.4438	317L	4438	4.890	4.178	5.283	55.292	18-13-3L	18.0	13.0	3.0
1.4818	S30415	153MA	2.385	2.039	2.578	26.976	153MA™	18.5	9.5	
1.4845	310S	4845	4.070	3.478	4.398	46.024	25-20	25.0	20.0	
1.4833	309S	4833	3.071	2.623	3.318	34.716	23-13	22.0	12.5	
1.4835	S30815	253MA	2.697	2.305	2.914	30.498	253MA®	21.0	11.0	
1.4539	904L	904L	6.763	5.779	7.308	76.477	904L	20.0	25.0	4.0
1.4547	S31254	254 SMO	6.763	5.779	7.308	76.474	254SMO®	20.0	18.0	6.0
1.4652	S32654	654 SMO	7.855	6.711	8.488	88.820	654 SMO®	24.0	22.0	7.3
1.4362	S32304	2304	2.289	1.955	2.473	25.873	2304	23.0	4.5	
1.4462	S31803	2205	3.575	3.054	3.863	40.424	2205	22.0	5.5	3.0
1.4410	S32750	2507	4.239	3.623	4.580	47.932	2507	25.0	7.0	4.0
1.4162	S32101	LDX2101	1.732	1.480	1.872	19.590	LDX2101®	21.0	1.5	
1.4828	-	4828	2.916	2.492	3.152	32.982	20-12Si	20.0	12.0	
1.4662	S82441	LDX2404	2.654	2.268	2.868	30.012	LDX2404™			
1.4003	S40977	4003	1.009	0.861	1.090	11.403	Ferritic			
1.4016	430	4016	1.142	0.976	1.234	12.918	Ferritic			
1.4509	441	4509	1.458	1.245	1.576	16.484	Ferritic			
1.4512	409	4512	0.966	0.826	1.043	10.920	Ferritic			
1.4521	444	4521	2.355	2.013	2.545	26.636	Ferritic			