

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - May 2024										
EN	ASTM	OSTP	Currency / Kgs				Old Ref GRADE	CR	NI	MO
			EUR	GBP	USD	SEK				
1.4301	304	4301	2.486	2.129	2.678	28.615	17-9	18.0	8-9	
1.4307	304L	4307	2.486	2.129	2.678	28.615	18-8L	18.0	8-9	
1.4306	304L	4306	2.737	2.343	2.949	31.500	18-10L	18.0	10.0	
1.4541	321	4541	2.708	2.318	2.918	31.171	18-10Ti	17.0	9.0	
1.4401	316	4401	4.025	3.445	4.336	46.325	17-11-2	16.5	10.0	2.0
1.4404	316L	4404	4.025	3.445	4.336	46.325	17-11-2L	16.5	10.0	2.0
1.4571	316Ti	4571	4.080	3.494	4.396	46.972	17-11-2Ti	16.5	10.5	2.0
1.4436	316	4436	4.385	3.754	4.724	50.476	17-11-2.5	16.5	10.5	2.5
1.4432	316L	4432	4.456	3.815	4.800	51.293	17-12-2.5L	16.5	10.5	2.5
1.4435	316L	4435	4.532	3.880	4.883	52.176	17-13-2.5L	17.0	12.5	2.5
1.4438	317L	4438	5.183	4.437	5.583	59.657	18-13-3L	18.0	13.0	3.0
1.4818	S30415	153MA	2.559	2.191	2.757	29.457	153MA™	18.5	9.5	
1.4845	310S	4845	4.428	3.790	4.769	50.959	25-20	25.0	20.0	
1.4833	309S	4833	3.312	2.835	3.567	38.121	23-13	22.0	12.5	
1.4835	S30815	253MA	2.895	2.478	3.119	33.322	253MA®	21.0	11.0	
1.4539	904L	904L	7.229	6.189	7.788	83.213	904L	20.0	25.0	4.0
1.4547	S31254	254 SMO	7.128	6.102	7.679	82.041	254SMO®	20.0	18.0	6.0
1.4652	S32654	654 SMO	8.288	7.096	8.929	95.402	654 SMO®	24.0	22.0	7.3
1.4362	S32304	2304	2.405	2.059	2.591	27.682	2304	23.0	4.5	
1.4462	S31803	2205	3.716	3.181	4.003	42.767	2205	22.0	5.5	3.0
1.4410	S32750	2507	4.414	3.779	4.755	50.806	2507	25.0	7.0	4.0
1.4162	S32101	LDX2101	1.783	1.526	1.921	20.523	LDX2101®	21.0	1.5	
1.4828	-	4828	3.144	2.691	3.387	36.186	20-12Si	20.0	12.0	
1.4662	S82441	LDX2404	2.754	2.358	2.967	31.700	LDX2404™			
1.4003	S40977	4003	1.026	0.879	1.105	11.812	Ferritic			
1.4016	430	4016	1.162	0.995	1.252	13.376	Ferritic			
1.4509	441	4509	1.477	1.264	1.590	16.998	Ferritic			
1.4512	409	4512	0.978	0.837	1.053	11.256	Ferritic			
1.4521	444	4521	2.391	2.047	2.576	27.523	Ferritic			