

# OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - December 2024										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,374	1,978	2,550	27,405	17-9	18,0	8-9	
1.4307	304L	4307	2,374	1,978	2,550	27,405	18-8L	18,0	8-9	
1.4306	304L	4306	2,599	2,167	2,791	30,012	18-10L	18,0	10,0	
1.4541	321	4541	2,570	2,144	2,761	29,685	18-10Ti	17,0	9,0	
1.4401	316	4401	3,963	3,304	4,256	45,760	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	3,963	3,304	4,256	45,760	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	4,014	3,345	4,310	46,339	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	4,333	3,612	4,654	50,035	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	4,419	3,685	4,747	51,034	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	4,464	3,723	4,796	51,555	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	5,119	4,268	5,498	59,110	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,441	2,036	2,622	28,191	153MA™	18,5	9,5	
1.4845	310S	4845	4,124	3,437	4,430	47,619	25-20	25,0	20,0	
1.4833	309S	4833	3,123	2,604	3,355	36,062	23-13	22,0	12,5	
1.4835	S30815	253MA	2,745	2,289	2,949	31,701	253MA®	21,0	11,0	
1.4539	904L	904L	7,058	5,883	7,581	81,497	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	7,156	5,965	7,685	82,630	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	8,296	6,916	8,910	95,793	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,376	1,980	2,552	27,434	2304	23,0	4,5	
1.4462	S31803	2205	3,792	3,160	4,072	43,781	2205	22,0	5,5	3,0
1.4410	S32750	2507	4,507	3,757	4,840	52,035	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,812	1,511	1,947	20,927	LDX2101®	21,0	1,5	
1.4828	-	4828	2,991	2,493	3,213	34,539	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	2,801	2,335	3,008	32,344	LDX2404™			
1.4003	S40977	4003	1,056	0,880	1,134	12,184	Ferritic			
1.4016	430	4016	1,195	0,996	1,283	13,792	Ferritic			
1.4509	441	4509	1,510	1,258	1,622	17,429	Ferritic			
1.4512	409	4512	1,014	0,845	1,089	11,708	Ferritic			
1.4521	444	4521	2,514	2,095	2,699	29,023	Ferritic			