

# OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - January 2025										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,432	2,017	2,554	28,029	17-9	18,0	8-9	
1.4307	304L	4307	2,432	2,017	2,554	28,029	18-8L	18,0	8-9	
1.4306	304L	4306	2,662	2,209	2,797	30,684	18-10L	18,0	10,0	
1.4541	321	4541	2,632	2,184	2,765	30,338	18-10Ti	17,0	9,0	
1.4401	316	4401	4,030	3,343	4,232	46,442	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	4,030	3,343	4,232	46,442	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	4,080	3,384	4,285	47,020	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	4,402	3,652	4,624	50,735	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	4,487	3,723	4,714	51,718	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	4,537	3,763	4,764	52,281	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	5,196	4,310	5,458	59,883	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,502	2,076	2,628	28,834	153MA™	18,5	9,5	
1.4845	310S	4845	4,219	3,501	4,432	48,627	25-20	25,0	20,0	
1.4833	309S	4833	3,198	2,653	3,359	36,854	23-13	22,0	12,5	
1.4835	S30815	253MA	2,812	2,333	2,953	32,408	253MA®	21,0	11,0	
1.4539	904L	904L	7,159	5,939	7,519	82,501	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	7,239	6,005	7,604	83,433	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	8,393	6,962	8,815	96,720	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,428	2,014	2,550	27,980	2304	23,0	4,5	
1.4462	S31803	2205	3,846	3,190	4,039	44,322	2205	22,0	5,5	3,0
1.4410	S32750	2507	4,567	3,788	4,797	52,629	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,852	1,535	1,945	21,333	LDX2101®	21,0	1,5	
1.4828	-	4828	3,062	2,540	3,215	35,287	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	2,849	2,363	2,992	32,829	LDX2404™			
1.4003	S40977	4003	1,086	0,900	1,141	12,515	Ferritic			
1.4016	430	4016	1,229	1,020	1,291	14,168	Ferritic			
1.4509	441	4509	1,543	1,280	1,622	17,788	Ferritic			
1.4512	409	4512	1,044	0,866	1,096	12,028	Ferritic			
1.4521	444	4521	2,548	2,114	2,676	29,366	Ferritic			