

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - February 2025										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,436	2,032	2,519	27,981	17-9	18,0	8-9	
1.4307	304L	4307	2,436	2,032	2,519	27,981	18-8L	18,0	8-9	
1.4306	304L	4306	2,665	2,223	2,755	30,614	18-10L	18,0	10,0	
1.4541	321	4541	2,636	2,199	2,724	30,274	18-10Ti	17,0	9,0	
1.4401	316	4401	4,050	3,379	4,187	46,528	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	4,050	3,379	4,187	46,528	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	4,101	3,420	4,239	47,104	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	4,426	3,693	4,576	50,850	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	4,514	3,766	4,667	51,857	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	4,560	3,804	4,714	52,384	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	5,224	4,359	5,402	60,019	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,506	2,090	2,590	28,781	153MA™	18,5	9,5	
1.4845	310S	4845	4,214	3,516	4,356	48,409	25-20	25,0	20,0	
1.4833	309S	4833	3,197	2,667	3,305	36,731	23-13	22,0	12,5	
1.4835	S30815	253MA	2,813	2,347	2,908	32,321	253MA®	21,0	11,0	
1.4539	904L	904L	7,191	5,998	7,434	82,603	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	7,292	6,084	7,538	83,766	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	8,450	7,050	8,737	97,081	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,438	2,034	2,521	28,006	2304	23,0	4,5	
1.4462	S31803	2205	3,877	3,234	4,008	44,530	2205	22,0	5,5	3,0
1.4410	S32750	2507	4,603	3,840	4,759	52,878	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,865	1,556	1,927	21,422	LDX2101®	21,0	1,5	
1.4828	-	4828	3,062	2,555	3,166	35,180	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	2,870	2,394	2,967	32,968	LDX2404™			
1.4003	S40977	4003	1,096	0,914	1,134	12,596	Ferritic			
1.4016	430	4016	1,239	1,033	1,280	14,227	Ferritic			
1.4509	441	4509	1,553	1,296	1,605	17,840	Ferritic			
1.4512	409	4512	1,055	0,880	1,090	12,112	Ferritic			
1.4521	444	4521	2,574	2,147	2,661	29,572	Ferritic			