

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - April 2025										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,406	2,008	2,574	26,629	17-9	18,0	8-9	
1.4307	304L	4307	2,406	2,008	2,574	26,629	18-8L	18,0	8-9	
1.4306	304L	4306	2,634	2,198	2,818	29,154	18-10L	18,0	10,0	
1.4541	321	4541	2,602	2,171	2,783	28,803	18-10Ti	17,0	9,0	
1.4401	316	4401	3,971	3,313	4,247	43,954	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	3,971	3,313	4,247	43,954	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	4,017	3,351	4,296	44,462	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	4,337	3,618	4,638	47,993	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	4,419	3,687	4,727	48,911	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	4,470	3,729	4,781	49,475	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	5,118	4,269	5,473	56,635	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,474	2,063	2,645	27,372	153MA™	18,5	9,5	
1.4845	310S	4845	4,173	3,482	4,464	46,192	25-20	25,0	20,0	
1.4833	309S	4833	3,159	2,636	3,380	34,972	23-13	22,0	12,5	
1.4835	S30815	253MA	2,780	2,320	2,973	30,764	253MA®	21,0	11,0	
1.4539	904L	904L	7,064	5,895	7,557	78,198	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	7,117	5,939	7,613	78,782	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	8,247	6,880	8,821	91,280	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,385	1,990	2,551	26,399	2304	23,0	4,5	
1.4462	S31803	2205	3,766	3,142	4,028	41,685	2205	22,0	5,5	3,0
1.4410	S32750	2507	4,468	3,727	4,778	49,450	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,817	1,516	1,944	20,112	LDX2101®	21,0	1,5	
1.4828	-	4828	3,033	2,530	3,243	33,562	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	2,790	2,328	2,984	30,882	LDX2404™			
1.4003	S40977	4003	1,076	0,898	1,151	11,917	Ferritic			
1.4016	430	4016	1,206	1,006	1,290	13,349	Ferritic			
1.4509	441	4509	1,519	1,267	1,625	16,810	Ferritic			
1.4512	409	4512	1,029	0,859	1,102	11,395	Ferritic			
1.4521	444	4521	2,493	2,080	2,667	27,600	Ferritic			