

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - June 2025										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,185	1,856	2,469	23,879	17-9	18,0	8-9	
1.4307	304L	4307	2,185	1,856	2,469	23,879	18-8L	18,0	8-9	
1.4306	304L	4306	2,391	2,031	2,701	26,129	18-10L	18,0	10,0	
1.4541	321	4541	2,363	2,008	2,670	25,826	18-10Ti	17,0	9,0	
1.4401	316	4401	3,591	3,051	4,057	39,245	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	3,591	3,051	4,057	39,245	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	3,635	3,088	4,107	39,714	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	3,919	3,329	4,429	42,829	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	3,994	3,393	4,511	43,638	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	4,040	3,432	4,564	44,146	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	4,622	3,926	5,222	50,506	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,246	1,908	2,537	24,538	153MA™	18,5	9,5	
1.4845	310S	4845	3,782	3,212	4,272	41,323	25-20	25,0	20,0	
1.4833	309S	4833	2,867	2,436	3,240	31,332	23-13	22,0	12,5	
1.4835	S30815	253MA	2,524	2,145	2,852	27,583	253MA®	21,0	11,0	
1.4539	904L	904L	6,383	5,421	7,211	69,739	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	6,425	5,458	7,259	70,204	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	7,444	6,324	8,410	81,343	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,175	1,847	2,456	23,757	2304	23,0	4,5	
1.4462	S31803	2205	3,412	2,899	3,855	37,286	2205	22,0	5,5	3,0
1.4410	S32750	2507	4,046	3,436	4,570	44,203	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,669	1,418	1,886	18,239	LDX2101®	21,0	1,5	
1.4828	-	4828	2,754	2,339	3,111	30,090	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	2,539	2,157	2,869	27,747	LDX2404™			
1.4003	S40977	4003	0,992	0,843	1,121	10,845	Ferritic			
1.4016	430	4016	1,114	0,946	1,258	12,170	Ferritic			
1.4509	441	4509	1,421	1,208	1,605	15,526	Ferritic			
1.4512	409	4512	0,943	0,802	1,066	10,307	Ferritic			
1.4521	444	4521	2,286	1,942	2,583	24,980	Ferritic			