

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - July 2025										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,151	1,817	2,454	23,480	17-9	18,0	8-9	
1.4307	304L	4307	2,151	1,817	2,454	23,480	18-8L	18,0	8-9	
1.4306	304L	4306	2,349	1,985	2,682	25,652	18-10L	18,0	10,0	
1.4541	321	4541	2,322	1,961	2,650	25,351	18-10Ti	17,0	9,0	
1.4401	316	4401	3,595	3,037	4,103	39,256	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	3,595	3,037	4,103	39,256	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	3,636	3,072	4,150	39,704	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	3,931	3,321	4,487	42,927	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	4,012	3,389	4,579	43,812	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	4,047	3,419	4,620	44,197	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	4,638	3,919	5,295	50,652	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,208	1,865	2,521	24,116	153MA™	18,5	9,5	
1.4845	310S	4845	3,693	3,120	4,216	40,328	25-20	25,0	20,0	
1.4833	309S	4833	2,809	2,374	3,207	30,685	23-13	22,0	12,5	
1.4835	S30815	253MA	2,478	2,094	2,829	27,064	253MA®	21,0	11,0	
1.4539	904L	904L	6,381	5,391	7,284	69,684	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	6,499	5,490	7,419	70,968	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	7,520	6,354	8,585	82,126	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,164	1,829	2,470	23,636	2304	23,0	4,5	
1.4462	S31803	2205	3,460	2,923	3,950	37,789	2205	22,0	5,5	3,0
1.4410	S32750	2507	4,106	3,468	4,686	44,835	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,673	1,413	1,910	18,270	LDX2101®	21,0	1,5	
1.4828	-	4828	2,700	2,282	3,082	29,485	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	2,562	2,164	2,924	27,975	LDX2404™			
1.4003	S40977	4003	1,007	0,851	1,150	11,000	Ferritic			
1.4016	430	4016	1,127	0,952	1,287	12,307	Ferritic			
1.4509	441	4509	1,424	1,203	1,625	15,549	Ferritic			
1.4512	409	4512	0,950	0,803	1,084	10,368	Ferritic			
1.4521	444	4521	2,336	1,973	2,667	25,508	Ferritic			