

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - August 2025										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,109	1,814	2,466	23,574	17-9	18,0	8-9	
1.4307	304L	4307	2,109	1,814	2,466	23,574	18-8L	18,0	8-9	
1.4306	304L	4306	2,284	1,964	2,670	25,529	18-10L	18,0	10,0	
1.4541	321	4541	2,282	1,963	2,668	25,505	18-10Ti	17,0	9,0	
1.4401	316	4401	3,555	3,057	4,155	39,724	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	3,555	3,057	4,155	39,724	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	3,593	3,090	4,201	40,157	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	3,856	3,317	4,508	43,094	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	3,938	3,387	4,605	44,015	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	3,966	3,411	4,637	44,330	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	4,548	3,912	5,318	50,839	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,151	1,849	2,514	24,035	153MA™	18,5	9,5	
1.4845	310S	4845	3,628	3,120	4,241	40,549	25-20	25,0	20,0	
1.4833	309S	4833	2,730	2,348	3,192	30,514	23-13	22,0	12,5	
1.4835	S30815	253MA	2,410	2,073	2,819	26,943	253MA®	21,0	11,0	
1.4539	904L	904L	6,239	5,365	7,293	69,722	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	6,397	5,503	7,480	71,506	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	7,400	6,364	8,651	82,706	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,132	1,833	2,492	23,826	2304	23,0	4,5	
1.4462	S31803	2205	3,428	2,947	4,008	38,310	2205	22,0	5,5	3,0
1.4410	S32750	2507	4,069	3,499	4,756	45,476	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,658	1,427	1,939	18,539	LDX2101®	21,0	1,5	
1.4828	-	4828	2,620	2,253	3,062	29,282	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	2,538	2,184	2,968	28,373	LDX2404™			
1.4003	S40977	4003	0,995	0,856	1,164	11,121	Ferritic			
1.4016	430	4016	1,121	0,964	1,310	12,527	Ferritic			
1.4509	441	4509	1,418	1,219	1,657	15,841	Ferritic			
1.4512	409	4512	0,941	0,808	1,099	10,509	Ferritic			
1.4521	444	4521	2,331	2,006	2,726	26,059	Ferritic			