

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - March 2026										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,436	2,117	2,849	26,241	17-9	18,0	8-9	
1.4307	304L	4307	2,436	2,117	2,849	26,241	18-8L	18,0	8-9	
1.4306	304L	4306	2,622	2,280	3,067	28,257	18-10L	18,0	10,0	
1.4541	321	4541	2,644	2,300	3,094	28,492	18-10Ti	17,0	9,0	
1.4401	316	4401	4,004	3,482	4,684	43,147	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	4,004	3,482	4,684	43,147	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	4,051	3,524	4,739	43,659	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	4,306	3,744	5,037	46,396	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	4,385	3,813	5,130	47,256	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	4,444	3,864	5,198	47,884	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	5,089	4,425	5,952	54,834	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,456	2,137	2,874	26,470	153MA™	18,5	9,5	
1.4845	310S	4845	4,299	3,738	5,029	46,319	25-20	25,0	20,0	
1.4833	309S	4833	3,154	2,743	3,690	33,992	23-13	22,0	12,5	
1.4835	S30815	253MA	2,768	2,407	3,237	29,822	253MA®	21,0	11,0	
1.4539	904L	904L	7,100	6,174	8,305	76,505	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	7,089	6,164	8,292	76,380	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	8,227	7,154	9,623	88,647	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,361	2,053	2,761	25,436	2304	23,0	4,5	
1.4462	S31803	2205	3,696	3,214	4,323	39,822	2205	22,0	5,5	3,0
1.4410	S32750	2507	4,390	3,817	5,135	47,294	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,803	1,569	2,109	19,432	LDX2101®	21,0	1,5	
1.4828	-	4828	3,031	2,636	3,545	32,661	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	2,757	2,397	3,225	29,702	LDX2404™			
1.4003	S40977	4003	1,051	0,914	1,229	11,329	Ferritic			
1.4016	430	4016	1,170	1,017	1,369	12,602	Ferritic			
1.4509	441	4509	1,469	1,278	1,718	15,829	Ferritic			
1.4512	409	4512	0,982	0,854	1,149	10,582	Ferritic			
1.4521	444	4521	2,417	2,102	2,827	26,042	Ferritic			