

# OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - March										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,463	2,141	2,918	26,143	17-9	18,0	8-9	
1.4307	304L	4307	2,463	2,141	2,918	26,143	18-8L	18,0	8-9	
1.4306	304L	4306	2,658	2,310	3,148	28,199	18-10L	18,0	10,0	
1.4541	321	4541	2,681	2,330	3,174	28,443	18-10Ti	17,0	9,0	
1.4401	316	4401	4,185	3,637	4,955	44,398	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	4,185	3,637	4,955	44,398	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	4,234	3,680	5,014	44,924	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	4,520	3,928	5,352	47,957	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	4,614	4,010	5,464	48,956	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	4,662	4,053	5,521	49,474	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	5,361	4,660	6,349	56,888	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,489	2,163	2,947	26,409	153MA™	18,5	9,5	
1.4845	310S	4845	4,379	3,807	5,185	46,462	25-20	25,0	20,0	
1.4833	309S	4833	3,203	2,783	3,793	33,980	23-13	22,0	12,5	
1.4835	S30815	253MA	2,804	2,437	3,319	29,744	253MA®	21,0	11,0	
1.4539	904L	904L	7,481	6,502	8,858	79,374	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	7,557	6,568	8,948	80,177	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	8,775	7,627	10,391	93,106	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,404	2,090	2,846	25,505	2304	23,0	4,5	
1.4462	S31803	2205	3,899	3,388	4,616	41,361	2205	22,0	5,5	3,0
1.4410	S32750	2507	4,651	4,042	5,507	49,344	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,827	1,588	2,163	19,383	LDX2101®	21,0	1,5	
1.4828	-	4828	3,076	2,674	3,643	32,645	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	2,864	2,489	3,391	30,384	LDX2404™			
1.4003	S40977	4003	1,042	0,906	1,234	11,061	Ferritic			
1.4016	430	4016	1,155	1,004	1,367	12,256	Ferritic			
1.4509	441	4509	1,455	1,265	1,723	15,441	Ferritic			
1.4512	409	4512	0,971	0,844	1,149	10,298	Ferritic			
1.4521	444	4521	2,528	2,197	2,993	26,818	Ferritic			