

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - April										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,552	2,216	2,967	27,310	17-9	18,0	8-9	
1.4307	304L	4307	2,552	2,216	2,967	27,310	18-8L	18,0	8-9	
1.4306	304L	4306	2,752	2,390	3,199	29,448	18-10L	18,0	10,0	
1.4541	321	4541	2,774	2,408	3,225	29,679	18-10Ti	17,0	9,0	
1.4401	316	4401	4,399	3,820	5,114	47,078	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	4,399	3,820	5,114	47,078	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	4,451	3,865	5,174	47,628	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	4,763	4,137	5,538	50,976	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	4,869	4,229	5,660	52,107	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	4,909	4,263	5,707	52,534	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	5,653	4,909	6,573	60,504	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,581	2,241	3,000	27,615	153MA™	18,5	9,5	
1.4845	310S	4845	4,514	3,919	5,247	48,303	25-20	25,0	20,0	
1.4833	309S	4833	3,313	2,877	3,851	35,453	23-13	22,0	12,5	
1.4835	S30815	253MA	2,903	2,521	3,374	31,060	253MA®	21,0	11,0	
1.4539	904L	904L	7,856	6,822	9,133	84,070	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	8,017	6,962	9,321	85,797	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	9,312	8,086	10,826	99,649	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,525	2,193	2,936	27,022	2304	23,0	4,5	
1.4462	S31803	2205	4,153	3,606	4,829	44,444	2205	22,0	5,5	3,0
1.4410	S32750	2507	4,960	4,308	5,767	53,082	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,934	1,679	2,248	20,697	LDX2101®	21,0	1,5	
1.4828	-	4828	3,177	2,760	3,695	34,010	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	3,045	2,644	3,540	32,583	LDX2404™			
1.4003	S40977	4003	1,094	0,950	1,272	11,706	Ferritic			
1.4016	430	4016	1,218	1,058	1,417	13,038	Ferritic			
1.4509	441	4509	1,520	1,320	1,768	16,267	Ferritic			
1.4512	409	4512	1,024	0,889	1,190	10,951	Ferritic			
1.4521	444	4521	2,699	2,344	3,138	28,889	Ferritic			