

OSTP

AAF / Alloy Adjustment Factor

| AAF for welded tubes and pipes - May | | | | | | | | | | |
|--------------------------------------|--------|---------|----------------|-------|--------|--------|------------|------|------|-----|
| | | | Currency / Kgs | | | | Old Ref | | | |
| EN | ASTM | OSTP | EUR | GBP | USD | SEK | GRADE | CR | NI | MO |
| 1.4301 | 304 | 4301 | 2,584 | 2,246 | 3,005 | 28,067 | 17-9 | 18,0 | 8-9 | |
| 1.4307 | 304L | 4307 | 2,584 | 2,246 | 3,005 | 28,067 | 18-8L | 18,0 | 8-9 | |
| 1.4306 | 304L | 4306 | 2,783 | 2,418 | 3,236 | 30,224 | 18-10L | 18,0 | 10,0 | |
| 1.4541 | 321 | 4541 | 2,805 | 2,437 | 3,261 | 30,461 | 18-10Ti | 17,0 | 9,0 | |
| 1.4401 | 316 | 4401 | 4,391 | 3,816 | 5,106 | 47,687 | 17-11-2 | 16,5 | 10,0 | 2,0 |
| 1.4404 | 316L | 4404 | 4,391 | 3,816 | 5,106 | 47,687 | 17-11-2L | 16,5 | 10,0 | 2,0 |
| 1.4571 | 316Ti | 4571 | 4,442 | 3,861 | 5,166 | 48,246 | 17-11-2Ti | 16,5 | 10,5 | 2,0 |
| 1.4436 | 316 | 4436 | 4,746 | 4,124 | 5,519 | 51,545 | 17-11-2.5 | 16,5 | 10,5 | 2,5 |
| 1.4432 | 316L | 4432 | 4,848 | 4,212 | 5,637 | 52,648 | 17-12-2.5L | 16,5 | 10,5 | 2,5 |
| 1.4435 | 316L | 4435 | 4,891 | 4,250 | 5,688 | 53,117 | 17-13-2.5L | 17,0 | 12,5 | 2,5 |
| 1.4438 | 317L | 4438 | 5,622 | 4,885 | 6,538 | 61,054 | 18-13-3L | 18,0 | 13,0 | 3,0 |
| 1.4818 | S30415 | 153MA | 2,614 | 2,271 | 3,039 | 28,384 | 153MA™ | 18,5 | 9,5 | |
| 1.4845 | 310S | 4845 | 4,538 | 3,943 | 5,277 | 49,286 | 25-20 | 25,0 | 20,0 | |
| 1.4833 | 309S | 4833 | 3,343 | 2,905 | 3,887 | 36,300 | 23-13 | 22,0 | 12,5 | |
| 1.4835 | S30815 | 253MA | 2,934 | 2,548 | 3,411 | 31,854 | 253MA® | 21,0 | 11,0 | |
| 1.4539 | 904L | 904L | 7,794 | 6,772 | 9,062 | 84,635 | 904L | 20,0 | 25,0 | 4,0 |
| 1.4547 | S31254 | 254 SMO | 7,929 | 6,890 | 9,220 | 86,106 | 254SMO® | 20,0 | 18,0 | 6,0 |
| 1.4652 | S32654 | 654 SMO | 9,206 | 7,999 | 10,705 | 99,975 | 654 SMO® | 24,0 | 22,0 | 7,3 |
| 1.4362 | S32304 | 2304 | 2,551 | 2,216 | 2,966 | 27,694 | 2304 | 23,0 | 4,5 | |
| 1.4462 | S31803 | 2205 | 4,135 | 3,594 | 4,809 | 44,909 | 2205 | 22,0 | 5,5 | 3,0 |
| 1.4410 | S32750 | 2507 | 4,929 | 4,283 | 5,730 | 53,521 | 2507 | 25,0 | 7,0 | 4,0 |
| 1.4162 | S32101 | LDX2101 | 1,964 | 1,707 | 2,284 | 21,326 | LDX2101® | 21,0 | 1,5 | |
| 1.4828 | - | 4828 | 3,207 | 2,786 | 3,729 | 34,827 | 20-12Si | 20,0 | 12,0 | |
| 1.4662 | S82441 | LDX2404 | 3,052 | 2,652 | 3,549 | 33,141 | LDX2404™ | | | |
| 1.4003 | S40977 | 4003 | 1,132 | 0,983 | 1,317 | 12,294 | Ferritic | | | |
| 1.4016 | 430 | 4016 | 1,258 | 1,093 | 1,463 | 13,660 | Ferritic | | | |
| 1.4509 | 441 | 4509 | 1,559 | 1,355 | 1,814 | 16,937 | Ferritic | | | |
| 1.4512 | 409 | 4512 | 1,063 | 0,923 | 1,235 | 11,536 | Ferritic | | | |
| 1.4521 | 444 | 4521 | 2,705 | 2,349 | 3,145 | 29,369 | Ferritic | | | |