

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - June										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,712	2,351	3,174	29,420	17-9	18,0	8-9	
1.4307	304L	4307	2,712	2,351	3,174	29,420	18-8L	18,0	8-9	
1.4306	304L	4306	2,933	2,542	3,432	31,811	18-10L	18,0	10,0	
1.4541	321	4541	2,954	2,561	3,458	32,055	18-10Ti	17,0	9,0	
1.4401	316	4401	4,637	4,019	5,428	50,311	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	4,637	4,019	5,428	50,311	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	4,693	4,068	5,494	50,923	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	5,020	4,350	5,875	54,464	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	5,127	4,444	6,001	55,619	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	5,180	4,490	6,063	56,196	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	5,960	5,166	6,977	64,669	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,749	2,382	3,217	29,820	153MA™	18,5	9,5	
1.4845	310S	4845	4,831	4,187	5,655	52,415	25-20	25,0	20,0	
1.4833	309S	4833	3,533	3,062	4,135	38,334	23-13	22,0	12,5	
1.4835	S30815	253MA	3,088	2,676	3,614	33,498	253MA®	21,0	11,0	
1.4539	904L	904L	8,316	7,207	9,734	90,221	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	8,409	7,289	9,843	91,236	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	9,770	8,469	11,437	106,007	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,637	2,286	3,088	28,615	2304	23,0	4,5	
1.4462	S31803	2205	4,315	3,740	5,050	46,811	2205	22,0	5,5	3,0
1.4410	S32750	2507	5,155	4,468	6,034	55,933	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	1,993	1,727	2,332	21,623	LDX2101®	21,0	1,5	
1.4828	-	4828	3,391	2,939	3,970	36,800	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	3,153	2,734	3,692	34,213	LDX2404™			
1.4003	S40977	4003	1,137	0,986	1,332	12,342	Ferritic			
1.4016	430	4016	1,251	1,084	1,465	13,580	Ferritic			
1.4509	441	4509	1,553	1,346	1,817	16,848	Ferritic			
1.4512	409	4512	1,060	0,919	1,241	11,498	Ferritic			
1.4521	444	4521	2,766	2,398	3,237	30,008	Ferritic			