

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - August										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,562	2,197	2,926	28,311	17-9	18,0	8-9	
1.4307	304L	4307	2,562	2,197	2,926	28,311	18-8L	18,0	8-9	
1.4306	304L	4306	2,757	2,363	3,148	30,459	18-10L	18,0	10,0	
1.4541	321	4541	2,778	2,382	3,173	30,704	18-10Ti	17,0	9,0	
1.4401	316	4401	4,591	3,935	5,242	50,727	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	4,591	3,935	5,242	50,727	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	4,644	3,980	5,302	51,300	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	4,996	4,283	5,704	55,197	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	5,123	4,392	5,850	56,609	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	5,137	4,403	5,865	56,758	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	5,941	5,092	6,783	65,632	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,592	2,222	2,960	28,642	153MA™	18,5	9,5	
1.4845	310S	4845	4,485	3,844	5,121	49,552	25-20	25,0	20,0	
1.4833	309S	4833	3,311	2,838	3,780	36,576	23-13	22,0	12,5	
1.4835	S30815	253MA	2,906	2,491	3,318	32,110	253MA®	21,0	11,0	
1.4539	904L	904L	8,201	7,030	9,363	90,599	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	8,559	7,338	9,774	94,575	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	9,925	8,508	11,331	109,649	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,608	2,236	2,979	28,818	2304	23,0	4,5	
1.4462	S31803	2205	4,455	3,819	5,086	49,225	2205	22,0	5,5	3,0
1.4410	S32750	2507	5,336	4,575	6,093	58,957	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	2,019	1,731	2,306	22,309	LDX2101®	21,0	1,5	
1.4828	-	4828	3,199	2,743	3,654	35,353	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	3,234	2,772	3,692	35,725	LDX2404™			
1.4003	S40977	4003	1,132	0,971	1,293	12,506	Ferritic			
1.4016	430	4016	1,266	1,086	1,446	13,993	Ferritic			
1.4509	441	4509	1,596	1,369	1,823	17,641	Ferritic			
1.4512	409	4512	1,066	0,914	1,217	11,777	Ferritic			
1.4521	444	4521	2,946	2,525	3,364	32,551	Ferritic			