

OSTP

AAF / Alloy Adjustment Factor

AAF for welded tubes and pipes - September										
			Currency / Kgs				Old Ref			
EN	ASTM	OSTP	EUR	GBP	USD	SEK	GRADE	CR	NI	MO
1.4301	304	4301	2,570	2,198	2,957	28,308	17-9	18,0	8-9	
1.4307	304L	4307	2,570	2,198	2,957	28,308	18-8L	18,0	8-9	
1.4306	304L	4306	2,768	2,367	3,183	30,482	18-10L	18,0	10,0	
1.4541	321	4541	2,790	2,385	3,209	30,727	18-10Ti	17,0	9,0	
1.4401	316	4401	4,654	3,979	5,352	51,252	17-11-2	16,5	10,0	2,0
1.4404	316L	4404	4,654	3,979	5,352	51,252	17-11-2L	16,5	10,0	2,0
1.4571	316Ti	4571	4,706	4,024	5,412	51,829	17-11-2Ti	16,5	10,5	2,0
1.4436	316	4436	5,070	4,336	5,832	55,842	17-11-2.5	16,5	10,5	2,5
1.4432	316L	4432	5,203	4,449	5,983	57,303	17-12-2.5L	16,5	10,5	2,5
1.4435	316L	4435	5,214	4,459	5,996	57,421	17-13-2.5L	17,0	12,5	2,5
1.4438	317L	4438	6,036	5,161	6,943	66,480	18-13-3L	18,0	13,0	3,0
1.4818	S30415	153MA	2,601	2,224	2,991	28,647	153MA™	18,5	9,5	
1.4845	310S	4845	4,514	3,859	5,192	49,717	25-20	25,0	20,0	
1.4833	309S	4833	3,326	2,844	3,825	36,632	23-13	22,0	12,5	
1.4835	S30815	253MA	2,918	2,494	3,356	32,131	253MA®	21,0	11,0	
1.4539	904L	904L	8,343	7,133	9,594	91,882	904L	20,0	25,0	4,0
1.4547	S31254	254 SMO	8,729	7,464	10,038	96,132	254SMO®	20,0	18,0	6,0
1.4652	S32654	654 SMO	10,119	8,653	11,637	111,441	654 SMO®	24,0	22,0	7,3
1.4362	S32304	2304	2,620	2,240	3,013	28,855	2304	23,0	4,5	
1.4462	S31803	2205	4,523	3,867	5,201	49,809	2205	22,0	5,5	3,0
1.4410	S32750	2507	5,423	4,638	6,238	59,731	2507	25,0	7,0	4,0
1.4162	S32101	LDX2101	2,021	1,728	2,324	22,256	LDX2101®	21,0	1,5	
1.4828	-	4828	3,215	2,750	3,698	35,415	20-12Si	20,0	12,0	
1.4662	S82441	LDX2404	3,266	2,792	3,756	35,971	LDX2404™			
1.4003	S40977	4003	1,125	0,961	1,294	12,384	Ferritic			
1.4016	430	4016	1,256	1,074	1,444	13,833	Ferritic			
1.4509	441	4509	1,586	1,356	1,824	17,467	Ferritic			
1.4512	409	4512	1,057	0,904	1,216	11,643	Ferritic			
1.4521	444	4521	2,980	2,547	3,427	32,814	Ferritic			